

Data sheet article FE-S-25-10

Technical data and application safety

Webcraft GmbH Industriepark 206 78244 Gottmadingen, Germany

Phone: +49 7731 939 839 1

www.supermagnete.fi support@supermagnete.fi

1. Technical information

Disc magnet Ø 25 mm, height 10 mm, holds approx. 1,5 kg, ferrite, Y35, no coating

Displacement force	FE-S-25-10 7640155432092 Ferrite Disc 25 mm(+/- 0,1 mm) 10 mm(+/- 0,1 mm) axial (parallel to height) No coating sintered Y35 approx. 1,5 kg (approx. 14 approx. 300 g (approx. 2,9 250°C
Manufacturing method	sintered
Strength	approx. 1,5 kg (approx. 14,7 N
Displacement force Max. working temperature Colour	
Weight	23,8074 g
Curie temperature	450 °C 4000-4100 G, 0.40-0.41 T
Residual magnetism Br	2.20-2.45 kOe, 175-195 kA/m

4 Product compliant with the latest European RoHS directive. RoHS

Product compliant with the latest European REACH regulation. REACH

2. Safety tips

Danger	Swallowing
0-14	Children could swallow small magnets. If several magnets are swallowed, they could get stuck in the intestine and cause perilous complications.
	Magnets are not toys! Make sure that children don't play with magnets.



Pacemaker

Magnets could affect the functioning of pacemakers and implanted heart defibrillators. • A pacemaker could switch into test mode and cause illness. • A heart defibrillator may stop working.

If you wear these devices keep sufficient distance to magnets: www.supermagnete.fi/faq/distance
Warn others who wear these devices from getting too close to magnets.

3. Handling and storing

	Magnets produce a far-reaching, strong magnetic field. They could damage TVs and laptops, computer hard drives, credit and ATM cards, data storage media, mechanical watches, hearing aids and speakers.
	 Keep magnets away from devices and objects that could be damaged by strong magnetic fields. Please refer to our table of recommended distances: www.supermagnete.fi/faq/distance

Notice	Influence on people
0	According to the current level of knowledge, magnetic fields of permanent magnets do not have a measurable positive or negative influence on people. It is unlikely that permanent magnets constitute a health risk, but it cannot be ruled out entirely.
	 For your own safety, avoid constant contact with magnets. Store large magnets at least one metre away from your body.

Notice	Temperature resistance
	Ferrite magnets can be used at temperatures between -40°C and 250°C. At lower and higher temperatures they lose part of their adhesive force permanently.
	Don't use ferrite magnets in places where they are exposed to temperatures below -40°C or above 250°C.
Notice	Mechanical treatment

Houce	
	Ferrite magnets are brittle. When drilling or sawing a magnet with improper tools, the magnet may break.
U	Stay away from mechanical treatment of magnets if you do not possess the necessary equipment and experience.

4. Transportation tips

Caution	Airfreight
	Magnetic fields of improperly packaged magnets could influence airplane navigation devices. In the worst case it could lead to an accident.
	 Airfreight magnets only in packaging with sufficient magnetic shielding. Please refer to the respective regulations: www.supermagnete.fi/faq/airfreight
Caution	Postage
	Magnetic fields of improperly packaged magnets could cause disturbances in sorting machines and damage fragile goods in other packages.
	 Please refer to our shipping tips: www.supermagnete.fi/faq/shipping Use a large box and place the magnet in the middle surrounded by lots of padding material. Arrange magnets in a package in a way that the magnetic fields neutralise each other.

- If necessary, use sheet iron to shield the magnetic field.
- There are stricter rules for airfreight: Refer to the warning notice "Airfreight".

TARIC-Code: 8505 1910 90 0

Origin: China

For more information about magnets please review **https://www.supermagnete.fi/faqs**.

Last update: 23/11/2024